

IEC 60320 Appliance and Interconnection Couplers

Appliance Couplers					
Connectors		Inlets		Plug Connectors	Outlets
 C1 (non-rewireable only)	Class II Cold	 C2	0.2A Family	These couplers are not in the standard.	
 C5 (non-rewireable only)	Class I Cold	 C6	2.5A International/ 7A or 2.5A North American Family	 SHEET A (non-rewireable only)	Class I  SHEET B
 C7 (non-rewireable only)	Class II Cold	 C8		 SHEET C (non-rewireable only)	Class II  SHEET D
 C9 (non-rewireable only)	Class II Cold	 C10	6A Family	These couplers are not in the standard.	
 C13	Class I Cold	 C14	10A International/ 15A North American Family	 SHEET E	Class I  SHEET F
 C15	Class I Hot	 C16		These couplers are not in the standard.	
 C15A	Class I Very Hot	 C16A		These couplers are not in the standard.	
 C17 (non-rewireable only)	Class II Cold	 C18		 SHEET G (non-rewireable only)	Class II  SHEET H
 C19	Class I Cold	 C20		 SHEET I	Class I  SHEET J
 C21	Class I Very Hot	 C22	16A International/ 20A North American Family	These couplers are not in the standard.	
 C23 (non-rewireable only)	Class II Cold	 C24		 SHEET K (non-rewireable only)	Class II  SHEET L

These couplers are for AC only, with a rated voltage not exceeding 250VAC and not exceeding the rated currents listed above for 50Hz or 60Hz power.



U.S.A.
100 Interpower Avenue, Oskaloosa, IA 52577
United States/Canada, Puerto Rico, Virgin Islands
Toll-Free Phone: (800) 662-2290 • Toll-Free Fax: (800) 645-5360
International
Phone: (641) 673-5000 • Fax: (641) 673-5100
E-mail: sales@interpower.com

UK
10 Kelvin Drive • Knowlhill, Milton Keynes
Buckinghamshire MK5 8NH
UK, Ireland, Germany, Switzerland, Austria
Freephone: 0800 5566 5566 • Freefax: 0800 5655 5655
International
Phone: +44 (0)1908 295300 • Fax: +44 (0)1908 295301
E-mail: uk@interpower.com